

## **BT>RJ45 Voice Kit-Port Doubler Version**

### Kit Contents

RJ45 Port Doubler & Cable Assembly (1)



**Fig 1**

RJ45 Port Doubler & BT Converter Assembly (1)



**Fig 2**

- (1) Plug RJ45 Port Doubler & Cable Assembly into patch panel port to be patched for Voice (& Shared for DATA) (Fig1)
- (2) Plug the BT Plug of the Cable Assembly into the BT line to be patched over the RJ45 Wiring. (Fig 1 Wiring Assembly)
- (3) Plug the DATA Patch Lead (NOT supplied) into the spare port on the RJ45 Doubler & Cable Assembly (Fig 1, Computer symbol on Port Doubler)
- (4) Ensure that the corresponding wall outlet has the RJ45 Port Doubler & BT Converter Assembly plugged in. (Fig 2)
- (5) Plug the DATA device into the spare port on the RJ45 Port Doubler & BT Converter Assembly. (Fig 2, Computer symbol on port doubler)(Cable not supplied)

You now have a DATA device & BT line patched over one RJ45 Cable!

### **NOTES**

**Telephone equipment uses what is known as a REN rating, the sum of all equipment connected MUST NOT exceed 4. Check equipment being connected to obtain the REN rating**

**run-IT-direct assumes no responsibility for damage caused by not adhering to these instructions**